

High Temperature Furnace (Up To 1400° C)

Make: LabTek

Model: SUN-026

Origin: India

Furnaces are offered in standard sizes from 0.5 to 7.5 cubic feet for applications to 2350 °F. All furnaces are ruggedly constructed and energy efficient, and a wide range of temperature controls are offered for every type of use. Custom features and sizes are also available upon request.

- 🍏 All furnaces are built with 3" premium insulating firebrick and 1" fiber board to permit rapid firing.
- 🍏 Elements are protected in dropped recessed side wall grooves to provide even heating, longer life, and easy replacement.
- 🍏 Outer shells are constructed using stainless steel to improve the casing resistance to high temperatures.
- 🍏 Front-loading and top-loading door styles are offered.
- 🍏 Alternate power requirements for domestic and international use are easily accommodated.
- 🍏 Replacement elements are available on a just-in-time basis.
- 🍏 All models are built with a standard multi-step temperature controller.



| Model | Inside Dimension |
|-------|--------------------------|
| 2927 | 8.50" x 9.00" x 8.75" |
| 2928 | 13.00" x 13.50" x 8.75" |
| 2929 | 22.00" x 22.00" x 13.50" |

Laboratory Incubator

Make: LabTek

Model: SUN-027

Origin: India

Incubators are designed fabricated & tested to suit various applications in growing field of Medical Agriculture. Research Laboratories of Hospital/Bio-Tech lab. Suitable to work on 230 V A.C. Supply 50 Hz.

Double walled construction outer body made of M.S. Duly stove enamel/powder coated, with inside Aluminium/Stainless Steel Chamber having 60-75mm glass wool insulation, door with glass window for observation of sample without disturbing. The door is fitted with heavy chrome plated hinge. Provided with adjustable Steel/Aluminium/Wire mesh tray. Temp is recorded means of "L" shaped Prismatic glass Thermometer fitted at the front of the cabinet Temperature controlled by Hydraulic type Bi-Metallic Capillary Thermostat, having adjustable air ventilators on both sides. Heating element are made from high grade (Kanthal) Resistant wire. Heaters are fitted/wound along all sides & bottom. Complete with 2 pilot lamp cord & plug pin etc.



Optional:

Air circulation can be fitted in all the above size at extra cost.

Digital Temp. Controller/Indicator can be fitted with air circulation system at system at extra cost if required.

Alarm system if required can be fitted against order.

Deluxe Model with Thermostat heavy Gauge Inside / Outside chamber.

| Available Size | No. Of Trays | Rating | Ltr. |
|-------------------|--------------|--------|------|
| 300 x 300 x 300mm | 2 | 500W | 28 |
| 350 x 350 x 350mm | 2 | 500W | 45 |
| 450 x 450 x 450mm | 2 | 500W | 95 |
| 450 x 450 x 605mm | 2 | 750W | 125 |
| 605 x 605 x 605mm | 2 | 1.0 kW | 224 |
| 605 x 605 x 900mm | 3 | 1.0 kW | 336 |
| 605 x 450 x 900mm | 3 | 1.0 kW | 252 |

Daily Rain Gauge

Model: SUN-028

Origin: India

With the aid of our proficient professionals, we have been able to come up with a gamut of Daily Rain Gauge.

Other detail:

Wide assortment of Daily Rain Gauge is offered to our prestigious clients.

These products for their easy installation and hassle free performance.

Constructed from copper, It has a 5" funnel, an inner receiving vessel and an outer body all of copper, and a plastic measuring cylinder graduated 0 to 10mm, 0.1mm (100 Divisions

Specification:

Copper Rain gauge with 127 diameter rim, Supplied with inner can be measuring calibrated in mm and inches.

